

**Now charges
at 5 Volts!**

DPX™ Technology PLUS from 

APPLICATION AND INSTALLATION INSTRUCTIONS FOR PIE PART # VW02/PC-POD2

Compatibility only includes vehicles equipped with a double DIN AM/FM/CASS/CD radio.
Factory external CD Changer will need to be disconnected prior to installation of VW02/PC-POD2.

Use with one of the following iPods:

mini G3 G4 nano (G1, G2, G3, G4, G5) video color photo
classic (G1, G2, G3) iPhone (2G, 3G, 3GS, 4G) touch (G1, G2, G3)

The VW02/PC-POD2 will utilize the CD Changer controls of the radio to control the iPod in the following manner:

CD Changer Controls	=	iPod Controls
Track Up		Song Up
Track Down		Song Down
Fast Forward		Fast Forward
Fast Rewind		Fast Rewind

NOTE: Track number on both radio and iPod may not correspond with one another.

The VW02/PC-POD2 will charge the iPod and will not disable the functions of the iPod while connected.
The VW02/PC-POD2 will automatically pause the iPod whenever the radio is not in the simulated iPod mode.

INSTALLATION:

CAUTION: BEFORE ANY CONNECTIONS ARE MADE, PIE STRONGLY RECOMMENDS THAT ALL CIRCUITS BE VERIFIED WITH A VOLTMETER BEFORE INTERFACING WITH THEM. ALWAYS SET THE PARKING BRAKE BEFORE WORKING ON ANY VEHICLE.

DO NOT force connectors together as pin damage may occur. This installation will be flawless if you take your time making the connections described below. Following the installation sequence below is critical to ensure proper recognition of the iPod by the factory radio.

Note: Volkswagen radios are code protected. Verify that the code is available before disconnecting battery.

1. Disconnect the negative battery terminal.
2. Remove factory radio.
3. Connect the VW02/PC-POD2 to the 12-Pin CD Changer connector on the back of the radio.
4. Route the iPod dock cable from the VW02/PC-POD2 to the desired location.
5. Reinstall factory radio.
6. Reconnect the negative battery terminal.

VERIFY OPERATION:

1. Connect iPod to dock connector.
2. Turn radio on and press the CD Changer button.
3. Perform basic control test (Song up/down, FF/RW, etc) from the radio.
4. Perform control test on iPod (Playlist select, Random, Artist Search, Album Search, etc.)
5. Verify that the iPod is charging while the radio is turned on.
6. Change modes (AM, FM, CD, etc.). Verify that the iPod pauses while in the other modes.
7. Turn radio off and verify that the iPod shuts off also.

**APPLICATION AND INSTALLATION INSTRUCTIONS
FOR PIE PART # VW02/PC-POD2**

**INSTALLATION DIAGRAM
PIE PART # VW02/PC-POD2**

